

Statement of Suitability

Customer name : Soudal New Zealand Limited

Items :

- 110330 – Gorilla Pro Expanding Foam C&F – SNZ item 20088
- 110332 – Gorilla Pro Expanding Foam Aerosol – SNZ item 20048
- 117618 – Gorilla Fire Rated Expanding Foam C&F – SNZ item 20160
- 121867 – Gorilla Flexi Expanding Foam C&F – SNZ item 20041
- 127564 – Gorilla Smart Foam Expanding Foam – SNZ item 20250

The products mentioned above are Polyurethane Foams in aerosol cans.

These products have been manufactured by Soudal under the controls established by a quality management system that meets the requirements of ISO9001 : 2000 which has been independently certified by « Bureau Veritas Certification » under certificate number BEL 1001545

Based on our experience with this product range which has been in regular production for more than 30 years we can state that the products mentioned above are completely chemically inert once fully cured and therefore there is no risk Polyurethane Polymers leaching, migrating and attacking onto TPS wiring or any other cable coatings.

As the curing process is very short (between 1 hour and 24 hours depending on thickness of the extruded PU Foam material, temperature and humidity, there is virtually no risk of interaction with the coating material of cables used in electric and electronic applications.

We cannot exclude the possibility of plasticizers from TPS wiring to be leaching onto the cured Polyurethane Foams. We therefore recommend the use of « non migratory » TPS wiring if there is the possibility of direct contact. Alternatively, direct contact between TPS wiring and cured PU Foam can be avoided by wrapping the TPS wiring with PE or PP tapes.

Turnhout, 1 August 2019

Soudal NV

Gil Stamberger
Export Area Manager



Everdongenlaan 18 - 2300 Turnhout Belgium
SODAL